

G704T

LOW PROFILE CHEMICAL SPLASH GOGGLE

**PART**

EG704T**

LENS
 Clear (Anti-Fog)

- Indirect vent provides chemical splash protection.
- Lightweight goggle performs with superior protection.
- Low profile, modern sport design with anti-glare frame.
- Lenses provide 99% protection against harmful UV rays.
- Single polycarbonate lens is coated for anti-fog and scratch resistance.
- Adjustable elastic band and soft PVC frame provide comfort and custom fit.

GENERAL SPECIFICATION

Bridge: 21mm
Closest Point Between Lens: 18mm
Lens Base: 6 Curve
Lens Size Diagonal: 82mm
Lens Size Vertical: 52mm
Lens Thickness: 2mm - 2.2mm
Overall Width (Hinge-Hinge): 148mm
PD: 64mm
Weight: 35gm

G704T

LOW PROFILE CHEMICAL SPLASH GOGGLE

PACKAGING
Polybag: 1pc
Inner Box: 12 pcs
Case: 144 pcs

COMPONENT	MATERIAL	FEATURES
Nose Piece	N/A	Integrated with PVC Frame
Frame	PVC	Low-profile frame design
Strap	N/A	Elastic Strap
Lens	Polycarbonate	6 base curve
Side Shields	N/A	Integrated with PVC Frame
Connector	Nylon	Thin and modern design

PART	LENS	LENS MARKING	FRAME MARKING
EG704T	 Clear (Anti-Fog)	2C - 1.2 P 1 BT CE	P EN166 BT CE

LENS MARKING

Code (field of use):

2 or 3: UV Filter
5 or 6: Solar Filter

Color Perception:

C: Unimpaired color perception

Protection Class:

1.2 to 6: Degree of visible light filtration

Optical Class:

1: High optical quality / No optical distortion

Mechanical Strength:

S: Extra strong, resists a 22mm, 43g ball falling 1.30 m/s
F: Low energy impact, resists a 6mm, 0.86g at 45 m/s
B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s
A: High energy impact, resists a 6mm, 0.86g at 190 m/s

Symbols:

P: Manufacture Indication
N: Filter with Anti-Fog features
CE: European Standard

FRAME MARKING

Symbols:

CE: European Standard
P: Manufacture Indication
EN166: CE specification for protective eyewear

Mechanical Strength:

F: Low energy impact
B: Medium energy impact
BT: Medium energy impact at extreme temperatures

Protection Class:

3: Protection against liquid droplets
4: Protection against large dust