

# MINI ZTEK®

Better Suited For Smaller Facial Features



Black Temples

Part	Lens
ES2510SN•••	Clear
ES2515SN••	Coffee
ES2520SN•••	Gray
ES2530SN•••	Amber
ES2575SN•••	Blue Mirror
ES2580SN•••	Indoor/Outdoor Mirror

- Integrated nose piece.
- Soft, non-slip rubber temple tips provide non-binding fit.
- Economical wrap-around single lens provides full panoramic view.
- Mini Ztek has all the great features of Ztek® in a design better suited for smaller facial sizes.
- Lenses are coated for superior scratch resistance, provides 99.9% protection from harmful UV rays.

GENERAL SPECIFICATION
Bridge: 12mm
Lens Base: 10 Curve
Lens Size Diagonal: 73.8mm
Lens Size Vertical: 41mm
Lens Thickness: 2.3mm
Overall Length (Lens-Tip): 144mm
Overall Width (Hinge-Hinge): 128mm
PD: 50mm
Weight: 20gm
Closest point between lens: 15.2mm
Closest point between temple tips: 83mm

## PACKAGING

Polybag: 1pc
Inner Box: 12 pcs
Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	10 base curve, wrap around design with side protection
Frame	N/A	N/A
Side Shield	Polycarbonate	Integral to lens
Nose Piece	Polycarbonate	Universal, integral to lens
Sleeve (on temple)	N/A	N/A
Temple	Polycarbonate	Spatula with soft tip end
Temple Tips	PVC	Slip on the temple
Hinge	Polycarbonate	3 barrel type, integral to frame
Screw	Stainless Steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
ES2510SN	 Clear	2C - 1.2 P 1 S CE	CE P EN166 F
ES2515SN	 Coffee	5 - 2.5 P 1 S CE	CE P EN166 F
ES2520SN	 Gray	5 - 2.5 P 1 S CE	CE P EN166 F
ES2530SN	 Amber	2 - 1.2 P 1 S CE	CE P EN166 F
ES2575SN	 Blue Mirror	5 - 2.5 P 1 S CE	CE P EN166 F
ES2580SN	 Indoor/Outdoor Mirror	5 - 1.7 P 1 S CE	CE P EN166 F

## LENS MARKING

### Code (field of use):

2 or 3: UV Filter  
5 or 6: Solar Filter

### Color Perception:

C: Unimpaired color perception

### Protection Class:

1.2 to 6: Degree of visible light filtration

### Optical Class:

1: High optical quality / No optical distortion

### Mechanical Strength:

S: Extra strong, resists a 22mm, 43g ball falling 1.30 m/s  
F: Low energy impact, resists a 6mm, 0.86g at 45 m/s  
B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s  
A: High energy impact, resists a 6mm, 0.86g at 190 m/s

### Symbols:

P: Manufacture Indication  
N: Filter with Anti-Fog features  
CE: European Standard

## FRAME MARKING

### Symbols:

CE: European Standard  
P: Manufacture Indication  
EN166: CE specification for protective eyewear

### Mechanical Strength:

F: Low energy impact  
B: Medium energy impact  
BT: Medium energy impact at extreme temperatures

### Protection Class:

3: Protection against liquid droplets  
4: Protection against large dust