





OTS® XL

LENSES ARE 10% LARGER THAN THE OTS®



PART	LENS
ES7510SJ**	 Clear
ES7510STJ***	 Clear (Anti-Fog)
ES7520SJ**	 Gray
ES7580SJ**	 Indoor/Outdoor Mirror

- OTS® XL lenses are 10% larger than the OTS.
- Designed to better fit today's prescription eye wear.
- Lightweight nylon temples adjust for length and pitch.
- Single lens encapsulates the eyes for superb protection.
- Lenses coated for superior scratch resistance, provide 99.9% protection against UV rays.

GENERAL SPECIFICATION

Bridge: 21mm
Lens Base: 2 Curve
Lens Size Diagonal: 67mm
Lens Size Vertical: 53.4mm
Lens Thickness: 2.03mm
Overall Length (Lens-Tip): 147-160mm
Overall Width (Hinge-Hinge): 162mm
PD: 68mm
Weight: 34gm
Closest point between lens: 13.5mm
Closest point between temples tip: 85-87mm

PACKAGING

Polybag: 1pc





Inner Box: 12 pcs

Case: 300 pcs

OTS® XL

LENSES ARE 10% LARGER THAN THE OTS®

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	Wraparound with angle side protection
Side Shield	Polycarbonate	Angled
Nose Piece	Polycarbonate	Universal, integral to lens
Angle Adjust	Nylon	Ratchet type consist of 3 components
	Polycarbonate	
Sleeve	Nylon	4 lengths positions adjustment
Temples Tips	PVC	Spatula, soft & extendable
Hinge	Nylon	3 barrel type
Screw	Stainless steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
ES7510SJ	 Clear	2C - 1.2 P 1 F CE	CE P EN166 F
ES7510STJ	 Clear (Anti-Fog)	2C - 1.2 P 1 F N CE	CE P EN166 F
ES7520SJ	 Gray	5 - 2.5 P 1 F CE	CE P EN166 F
ES7580SJ	 Indoor/Outdoor Mirror	5 - 1.7 P 1 F CE	CE P EN166 F

LENS MARKING

Code (field of use):

2 or 3: UV Filter

5 or 6: Solar Filter

Color Perception:

C: Unimpaired color perception

Protection Class:

1.2 to 6: Degree of visible light filtration

Optical Class:

1: High optical quality / No optical distortion

Mechanical Strength:

S: Extra strong, resists a 22mm, 43g ball falling 1.30 m/s

F: Low energy impact, resists a 6mm, 0.86g at 45 m/s

B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s

A: High energy impact, resists a 6mm, 0.86g at 190 m/s

Symbols:

P: Manufacture Indication

N: Filter with Anti-Fog features

CE: European Standard

FRAME MARKING

Symbols:

CE: European Standard

P: Manufacture Indication

EN166: CE specification for protective eyewear

Mechanical Strength:

F: Low energy impact

B: Medium energy impact

BT: Medium energy impact at extreme temperatures

Protection Class:

3: Protection against liquid droplets

4: Protection against large dust