

Surface finishing Metal and Inox

LE 14-7 125 INOX Set

Order no. 364.614



1400 watt INOXFLEX, specialist for stainless steels and steel alloys, 125 mm

- VR microprocessor control: speed selection, tachogenerator constant speed control, soft start, restart protection after power failure, overload protection and temperature monitoring
- Highly efficient and resilient motor for more power output
- Special gearbox: special gear ratio for high torque in medium and low speed range. Prevents blue discolouration and distortion due to the development of heat.
- Completely cast electronic components prevents damage due to metal dust. The 3-fold winding protection reduces motor wear, increases service life
- SoftVib handgrip with integrated, patented locknut wrench and vibration damping
- Tool-free adjustment of safety guard
- Spindle lock

Technical attributes	LE 14-7 125 INOX Set
Max. disc diameter	125 mm
Max. polishing pad diameter	160 mm
No load speed	2100-7500 rpm
Power input	1400 watt
Power output	880 watt
Tool fixture	M 14
Weight	2,4 kg

Standard equipment	
1 guard 125 Ø	274.658
1 SoftVib handle	316.857
1 FixTec quick-clamp nut M 14	313.459
1 flap disc P 60	1 piece of 349.925
1 fillet weld disc 6 A medium	1 piece of 358.711
1 SC-VL polishing flap wheel medium	1 piece of 358.606
1 SC fleece disc coarse	1 piece of 358.614
1 SC fleece disc medium	1 piece of 358.622
1 SC fleece disc very fine	1 piece of 358.630
1 PyraFLEX A 160	1 piece of 364.592
1 PyraFLEX A 65	1 piece of 358.797
1 PyraFLEX A 45	1 piece of 358.800
1 PyraFLEX A 30	1 piece of 358.819
3 PolishFLEX Disc	3 pieces of 364.606

FLEX Elektrowerkzeuge GmbH

Bahnhofstrasse 15
D-71711 Steinheim/Murr
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Surface finishing Metal and Inox

Standard equipment

1 hook and loop grinding pad Hook	364.584
1 Poli set mini	365.041
1 case insert	367.206
1 plastic carry case	367.192