



| Allgemeintoleranzen für Längenmasse nach DIN ISO 2768-1 |                                    |              |               |                 |                  |                   |                    |
|---|------------------------------------|--------------|---------------|-----------------|------------------|-------------------|--------------------|
| Genauigkeitsgrad  | Abmasse in mm für Nennmassbereiche |              |               |                 |                  |                   |                    |
|   | 0.5<br>... 3                       | ≥ 3<br>... 6 | ≥ 6<br>... 30 | ≥ 30<br>... 120 | ≥ 120<br>... 400 | ≥ 400<br>... 1000 | ≥ 1000<br>... 2000 |
| μ (mittel)  | ± 0.1                              | ± 0.1        | ± 0.2         | ± 0.3           | ± 0.5            | ± 0.8             | ± 1.2              |

|     |               |       |      |   |  |  |          |                           |        |
|-----|---------------|-------|------|---|--|--|----------|---------------------------|--------|
|     |               |       |      | Geprüft                                       |  |  | Material | 1.4031(X39Cr13)           |        |
|     |               |       |      | Erstellt                                      |  |  | Gewicht  | 0.23 kg                   |        |
|     |               |       |      | Beschreibung                                  |  |  |          | Msst                      |        |
|     |               |       |      |   |  |  |          | 1:2                       |        |
|     |               |       |      |   |  |  |          | Blatt                     |        |
|     |               |       |      |   |  |  |          | 1 / 1                     |        |
| Ind | Änderungstext | Datum | Name | Index   |  |  |          | Zeichnungs- Artikelnummer | Format |
|     |               |       |      | <b>Bortolazzi Metallwaren, 8252 Schlatt</b>   |  |  |          | <b>22130</b>              | A3     |
|     |               |       |      | Tel. 0041 52 657 21 05 Fax. 0041 52 657 13 69 |  |  |          |                           |        |