

APEX 16X0,50 LO

PRODUCT DATA SHEET

This is to certify that the product supplied by us is manufactured according to quality procedures in compliance with ISO 9001, ISO14001, EN 13246.

We certify the product lead free.

Our tensile testing follows ISO 6892-1.

Produced in Sweden

| | | | | |
|----------------------------|----------------------|---|--|--|
| Product description | Product designation: | APEX 16X0,50 LO | | |
| | Item code: | 0616050 | | |
| | Material type: | Steel | | |
| | Material quality: | Standard | | |
| | Surface finish: | Black painted and waxed, deburred edges | | |

| | | | | | |
|-------------------------|--|--------|-------------|----------|------|
| Strap properties | Width (mm): | 16 | +0,05/-0,25 | | |
| | Thickness (mm): | 0.5 | +/-0,035 | | |
| | Elongation minimum - A100 (%): | 1 | | | |
| | Elongation minimum - A5 (%): | 4 | | | |
| | Break Strength (N): | Mini.: | 6360 | Average: | 7150 |
| | Tensile Strength (N/mm ²): | Mini.: | 800 | Average: | 890 |

| | | | | |
|----------------------|-------------------------------------|------------|--|--|
| Coils details | Winding: | Oscillated | | |
| | Coil Inside Diameter (mm): | 406 | | |
| | Coil Outside Diameter (mm): | 600 | | |
| | Coil Width (mm): | 60 | | |
| | Approximate Gross Coil Weight (kg): | 50 | | |

| | | | | |
|-----------------------|---------------------------------------|-------------|--|--|
| Pallet details | Package Dimensions (LxWxH): | 580*675*870 | | |
| | Number of Coils per Pallet: | 12 | | |
| | Coils axis on pallet: | Horizontal | | |
| | Approx. Gross Weight per Pallet (kg): | 600 | | |